

# Propane Gas best price Cylinder Gas Wholesale C3H8 Gas Propane

# **Basic Information**

. Place of Origin: China Brand Name: CMC · Certification: COA Model Number: C3h8 • Minimum Order Quantity: 1kg • Price: US \$2/kg Cylinder/Tank · Packaging Details: • Delivery Time: 15 days Payment Terms: L/C, T/T

• Supply Ability: 20000 Tons/Year



**Propane Gas** 

# **Product Specification**

• Product Name: Propane Gas

Cylinder Pressure: 12.5MPa/15MPa/20MPa
 Transport Package: 40L/47L/50L/118L/926L
 Specification: 40L/47L/50L/118L/926L

Trademark: CMC
Origin: China
HS Code: 2901100000
Supply Ability: 1,000,000ton/Year
Constituent: Industrial Pure Air

• Chemical Property: Combustion-Supporting Gas

Industrial Grade

Boiling Point: -42.1 °C
 Molecular Weight: 44.096
 Melting Point: -187.6 °C

Customization: Available | Customized Request



# More Images

Grade Standard:





## **Product Description**

# **Product Description**

Propane gas, also known as liquefied petroleum gas (LPG), is a flammable hydrocarbon gas composed primarily of propane (C3H8). Here are some key points about propane gas:

Chemical Formula: C3H8
Molecular Weight: 44.1 g/mol

Structure: Propane consists of three carbon atoms bonded to eight hydrogen atoms. It has a linear molecular structure and belongs to the alkane group.

Physical Properties: Propane is a colorless and odorless gas at room temperature and atmospheric pressure. However, an odorant called ethanethiol is added to propane for safety purposes, giving it a distinctive smell.

Production: Propane is produced as a byproduct of natural gas processing and petroleum refining. It is separated from other hydrocarbons through a process called fractionation or distillation.

Liquefaction: Propane can be easily liquefied under moderate pressure. This makes it convenient for storage, transportation, and domestic usage. Applications: Propane gas has a wide range of applications. It is commonly used as a fuel for heating homes, businesses, and industrial processes. It is also used as a fuel for cooking appliances such as stoves, ovens, and grills. Propane is utilized in the agricultural sector for crop drying and heating, as well as in the transportation sector as an alternative fuel for vehicles.

Safety Considerations: Propane is a flammable gas and should be handled with caution. Proper storage, transportation, and usage procedures must be followed to minimize the risk of leaks, fires, or explosions. Propane gas is heavier than air and can accumulate in poorly ventilated areas, posing a potential hazard.

Storage and Handling: Propane is typically stored and transported in pressurized containers, such as cylinders or tanks, designed to withstand the pressure of the gas. These containers should be stored in well-ventilated areas and kept away from sources of heat or ignition.

Environmental Impact: Propane is considered a cleaner-burning fuel compared to other fossil fuels. It produces lower levels of carbon dioxide and air pollutants when burned, resulting in reduced emissions and air pollution.

### **Product Description**

#### Basic Info.

| DOT Class         | 2.1                   | Un No               | 1075                |
|-------------------|-----------------------|---------------------|---------------------|
| Cylinde           | GB/ISO/DOT            | Cylinder Pressure   | 12.5MPa/15MPa/20MPa |
| Valve             | Cga350/Bwf-1          | Melting Point       | -187.6 ºC           |
| Appearance        | Colorless, Odorless   | Boiling Point       | -42.1 ºC            |
| Density           | 493 Kg/m <sup>3</sup> | Molecular Weight    | 44.096              |
| Transport Package | 40L/47L/50L/118L/926L | Specification       | 99.50%              |
| Trademark         | CMC                   | Origin              | China               |
| HS Code           | 29011000              | Production Capacity | 1, 000, 000ton/Year |

# Specification:

Dot Class:2.2 State: Liquid Purity: 99.5% UN NO: UN1978 CAS NO: 74-98-6

Grade Standard: Industrial Grade

| Specification    | ≥99.5 | %    |
|------------------|-------|------|
| Methane (CH4)    | ≤100  | ppmv |
| Ethane(C2H6)     | ≤250  | ppmv |
| Propylene(C3H6)  | ≤1000 | ppmv |
| Moisture(H2O)    | ≤3    | ppmv |
| Sulfur           | ≤1    | ppmv |
| Isobutane(C4H10) | ≤2500 | ppmv |
| N-butane(C4H10)  | ≤1000 | ppmv |

#### **Detailed Photos**



# Packaging & Shipping

Cylinder Specifications Contents
Cylinder Capacity Valve Weight
47L CGA350 19 kgs
118L BWF-1 45 kgs
926L BWF-1 375 kgs
ISO TANK 10 Tons

Company

Profile



Shanghai Kemike Chemical Co., Ltd is staffed by trained personnel, combine many years experience in Gas industry .We

supply cylinder gas, electronic gas, etc., and the gas holder, panel, valves and fittings and other equipment, parts and engineering services to our customers in China and worldwide; The products are involved in various industrial fields, such as semiconductor chip, solar cell, LED, TFT-LCD, optical fiber, glass, laser, medicine, etc., Our mission is to partner with our global customers to provide support, solutions and quality products that are innovative, reliable, and safe. Our products mainly include: H2, O2, N2, Ar, CO2, propane, acetylene, helium, laser mixed gas, SiH4, Sih2cl2, SiHCL3, SiCL4, NH3, CF4, NF3, SF6, HCL, N2O, doping mixed gas (TMB, PH3, B2H6) and other electronic gases.

CH3F H<sub>2</sub>S WF6 F6+CI2 SiCI4 NH<sub>3</sub> SiH4 NH<sub>3</sub> Kr HCI+Ne C3F8 **TEOS** SF<sub>6</sub> C2 4MS C3F8 CH4 PH<sub>3</sub> SiH<sub>2</sub> TMB+H2 CF4 C4F8 SiF4 **C3H8** CI2 He +As DCE Ge+Se **C3H6** BBr3 POCI3 N<sub>2</sub> **SO2** D+B CO+NO BC<sub>13</sub> D2 CO2 SiHCI3 CH2F2 AsH3 **C2H4** C2H2 HBr COS Ar+O2 HF Xe+NO **TMAI DMZn** DEZn GeH4 **C2H6 B2H6** H2Se GeCI4







