

China Factory Liquid Ammonia Cylinder Gas high purity Ammonia

Basic Information

. Place of Origin: China . Brand Name: CMC COA · Certification: Nh3 Model Number: • Minimum Order Quantity: 1kg • Price: US \$ 1/kg · Packaging Details: Cylinder/Tank • Delivery Time: 15 days Payment Terms: L/C, T/T . Supply Ability: 20000 Tons/Year



Product Specification

Product Name: Ammonia Gas
 Boiling Point: -33.5 °C
 Density: 0.73 Kg/M3
 Melting Point: -77.7 °C

• Cylinder Pressure: 3MPa/15MPa/20MPa

• Transport Package: 100L, 800L Specification: 100L, 800L CMC Trademark: · Origin: China . HS Code: 28141000 • Supply Ability: 20000 Tons/Year 7664-41-7 · CAS No.: Formula: Nh3 • EINECS: 231-635-3 Constituent: Industrial Pure Air



More Images









Product Description

Product Description

NH3 refers to ammonia, which is a chemical compound composed of one nitrogen atom bonded to three hydrogen atoms. Here are some key points about NH3:

Chemical Formula: NH3
Molecular Weight: 17.03 g/mol

Structure: Ammonia molecules have a trigonal pyramidal shape, with the nitrogen atom at the center and the three hydrogen atoms arranged around it

Physical Properties: Ammonia is a colorless gas with a distinct pungent odor. It has a boiling point of -33.34°C (-28.012°F) and a melting point of -77.73°C (-107.914°F) at standard pressure. It is highly soluble in water.

Production: Ammonia is primarily produced through the Haber-Bosch process, which involves the reaction of nitrogen gas (N2) and hydrogen gas (H2) under high pressure and temperature in the presence of a catalyst.

Uses: Ammonia has a wide range of applications. It is commonly used as a fertilizer in agriculture due to its high nitrogen content. It is also used as a refrigerant in industrial and commercial systems. Ammonia is an important precursor for the production of various chemicals, including fertilizers, plastics, explosives, and cleaning agents.

Basicity and Reactions: Ammonia is a weak base and can react with acids to form ammonium salts. It can also participate in various chemical reactions, such as with halogens to form ammonium halides or with metals to form metal amides.

Toxicity and Safety Considerations: Ammonia is toxic when inhaled in high concentrations. It can irritate the respiratory system, eyes, and skin. Exposure to high levels of ammonia vapor can be dangerous and even fatal. Proper ventilation and safety precautions should be followed when handling or working with ammonia.

Ammonia-Water Solution: Ammonia readily dissolves in water to form an aqueous solution called ammonium hydroxide or ammonia water. This solution is commonly used as a cleaning agent, and its concentration can vary depending on the intended application.

Basic Info.

Transport Package: 800L, 100L Melting Point -77.7 °C Trademark: CMC Boiling Point -33.5 °C

Specification 99.80% Production Capacity 20000 Tons/Year

Cylinder Pressure 3MPa/15MPa/20MPa Valve Qf-10

Product Description

Product Name	Ammonia
Chemical Formula	NH3
Hazard Class	2.3
Molecular Weight	17.031
UN	1005
Boiling Point(°C)	-33.43
Boiling Point(°F)	-241.17
Density(kg/m³)	0.728
Density(lb/ft³)	0.044

rocess:

Industrial ammonia is purified by a filter into the electronic grade ultra-high purity ammonia. The annual output of ultra-high purity ammonia gas in Jinhong is more than 10,000 tons.

Specification:

 S-cylinder: 44L/47L
 Valve: CGA660
 Content: 21Kg

 Y-cylinder: 440L
 Valve: DISS720
 Content: 230Kg

 T-cylinder: 930L
 Valve: DISS720
 Content:480Kg

 ISO tank: 22.5Nm³
 Valve:1""VCR"
 Content:11.2T

Application:

Ammonia(NH3)is used in

 metal treating operations as nitriding, carbo-nitriding, bright annealing, furnace brazing, sintering, sodium hydride descaling, atomic hydrogen welding, and other applications where protective atmospheres are required

2. hydrogenation of fats and oils as a convenient source of hydrogen

3.manufacturing of alkalis, ammonium salts, dyes, pharmaceuticals, cuprammonium rayon, and nylon

4. rubber industry for stabilization of raw latex to prevent coagulation during transportation and torage

5. as a catalyst in the phenol-formaldehyde condensation and also in the urea-formaldehyde condensation to make synthetic resin

6.produce proteins and can be used to improve the protein content of low quality hay

7.semiconductor industry

8.production of blue and white LEDs (Light Emitting Diods)

9.In the field of novel optoelectronic materials, it is an important base material for GAN preparation by MOCVD technology. High purity ammonia or the preparation of nitrogen trifluoride, silicon nitride, the basic material, is the production of super high nitrogen raw gas. In addition, liquid ammonia is widely used in the semiconductor industry, the metallurgical industry, as well as other industries and scientific research that need to protect the atmosphere.









Packaging & Shipping

Company

Profile



Shanghai Kemike Chemical Co., Ltd is staffed by trained personnel, combine many years experience in Gas industry .We supply cylinder gas, electronic gas, etc., and the gas holder, panel, valves and fittings and other equipment, parts and engineering services to our customers in China and worldwide; The products are involved in various industrial fields, such as semiconductor chip, solar cell, LED, TFT-LCD, optical fiber, glass, laser, medicine, etc., Our mission is to partner with our global customers to provide support, solutions and quality products that are innovative, reliable, and safe.

Our products mainly include: H2, O2, N2, Ar, CO2, propane, acetylene, helium, laser mixed gas, SiH4, Sih2cl2, SiHCL3, SiCL4, NH3, CF4, NF3, SF6, HCL, N2O, doping mixed gas (TMB, PH3, B2H6) and other electronic gases.

CH3F H₂S WF6 F6+Cl2 SiCI4 NH3 NH3 SiH4 Kr

SF₆ C2 HCI+Ne C3F8 **TEOS** CH4 PH₃ 4MS C3F8

SiH2 CF4 C4F8

AsH3

TMB+H2

SiF4 **C3H8** CI2 He +As

BBr3 C3H6 DCE Ge+Se

POCI3 N₂ **SO2** D+B

CO+NO BCI3 D2 CO₂ **C2H4**

C2H2

HBr

COS

Ar+O2

Xe+NO H2Se GeCI4 TMAI **DMZn** DEZn GeH4 **C2H6 B2H6**





SiHCI3

CH2F2

HF



Shanghai Kemike Chemical Co.,Ltd